

Type slang	Doorlaat slang		Pershuls		Inlagen	Schillengte		Hulscode	Pershuls	Persdiameter Ø +/- 0,1 mm	Pers- blok	Instelling
	inch	mm	Ø	mm		in	uit					
1 staalinlaag - dun rubber - Norm: EN 853-1SN / SAE 100 R1AT												
NST-HF 5	3/16	05	19,0	24,0	1			AD1-03	SFA-D1-05	14,8	14	0,8
NST-HF 6	1/4	06	22,0	24,7				AD1-04	SFA-D1-06	17,2	16	1,2
NST-HF 8	5/16	08	23,0	24,7				AD1-05	SFA-D1-08	18,9	16	2,9
NST-HF 10	3/8	10	26,0	29,7				AD1-06	SFA-D1-10	21,4	19	2,4
NST-HF 13	1/2	13	29,0	30,5				AD1-08	SFA-D1-13	24,7	23	1,7
NST-HF 16	5/8	16	32,0	30,5				AD1-10	SFA-D1-16	27,8	27	0,8
NST-HF 20	3/4	20	36,0	36,0				AD1-12	SFA-D1-20	31,7	31	0,7
NST-HF 25	1"	25	44,0	36,7				AD1-16	SFA-D1-25	39,4	39	0,4
2 staalinlagen - dun rubber - Norm: EN 853-2SN / SAE 100 R2AT												
HST-HF 5	3/16	05	21,0	24,0	2			AD2-03	SFA-D2-05	16,3	16	0,3
HST-HF 6	1/4	06	23,0	24,7				AD2-04	SFA-D2-06	18,2	16	2,2
HST-HF 8	5/16	08	25,0	24,7				AD2-05	SFA-D2-08	20,1	19	1,1
HST-HF 10	3/8	10	27,0	29,7				AD2-06	SFA-D2-10	22,3	19	3,3
HST-HF 13	1/2	13	30,0	30,5				AD2-08	SFA-D2-13	25,4	23	2,4
HST-HF 16	5/8	16	33,0	30,5				AD2-10	SFA-D2-16	28,8	27	1,8
HST-HF 20	3/4	20	37,0	36,0				AD2-12	SFA-D2-20	32,5	31	1,5
HST-HF 25	1"	25	45,0	36,7				AD2-16	SFA-D2-25	39,9	39	0,9
1 staalinlaag compact slang - Norm: EN 857-1SC												
NSK 6	1/4	06	22,0	24,7	1			AD1-04	SFA-D1-06	16,5	16	0,5
NSK 8	5/16	08	23,0	24,7				AD1-05	SFA-D1-08	18,1	16	2,1
NSK 10	3/8	10	26,0	29,7				AD1-06	SFA-D1-10	20,4	19	1,4
NSK 13	1/2	13	29,0	30,5				AD1-08	SFA-D1-13	23,9	23	0,9
2 staalinlagen compact slang - Norm: EN 857-2C												
HSK-HF 6	1/4	06	22,0	24,7	2			AD1-04	SFA-D1-06	17,4	16	1,4
HSK-HF 8	5/16	08	23,0	24,7				AD1-05	SFA-D1-08	19,1	19	0,1
HSK-HF 10	3/8	10	26,0	29,7				AD1-06	SFA-D1-10	21,2	19	2,2
HSK-HF 13	1/2	13	29,0	30,5				AD1-08	SFA-D1-13	24,8	23	1,8
HSK-HF 16	5/8	16	32,0	30,5				AD1-10	SFA-D1-16	27,9	27	0,9
HSK-HF 20	3/4	20	36,0	36,0				AD1-12	SFA-D1-20	31,7	31	0,7
HSK-HF 25	1"	25	44,0	36,7				AD1-16	SFA-D1-25	39,4	39	0,4
2 staalinlagen compact slang - Exceeds Norm: EN 857-2SC - SAE 100-R16												
HSK-PQ 6	1/4	06	22,0	24,7	2			AD1-04	SFA-D1-06	17,4	16	1,4
HSK-PQ 8	5/16	08	23,0	24,7				AD1-05	SFA-D1-08	18,9	16	2,9
HSK-PQ 10	3/8	10	26,0	29,7				AD1-06	SFA-D1-10	21,3	19	2,5
HSK-PQ 13	1/2	13	29,0	30,5				AD1-08	SFA-D1-13	25,1	23	2,1
HSK-PQ 16	5/8	16	32,0	30,5				AD1-10	SFA-D1-16	27,9	27	0,9
HSK-PQ 20	3/4	20	36,0	36,0				AD1-12	SFA-D1-20	31,7	31	0,7
HSK-PQ 25	1"	25	44,0	36,7				AD1-16	SFA-D1-25	39,8	39	0,8

Type slang	Doorlaat slang		Pershuls		Inlagen	Schillengte		Hulscode	Pershuls	Persdiameter Ø +/- 0,1 mm	Pers- blok	Instelling
	inch	mm	Ø	mm		in	uit					
4 staalinlagen - skive - Norm: SAE 100 R9R / DIN 20023 - 4SP / EN 856-4SP												
HDR 6	1/4	06	22,0	26,3	4		19,0	404-04	SFA-4S-06	18,5	16	2,5
HDR 10	3/8	10	25,0	28,5			19,0	404-06	SFA-4S-10	22,1	19	3,1
HDR 13	1/2	13	29,0	34,7			25,0	404-08	SFA-4S-13	26,4	23	3,4
HDR 16	5/8	16	33,0	37,5			28,0	404-10	SFA-4S-16	29,2	27	2,2
HDR 20	3/4	20	37,0	41,5			33,0	404-12	SFA-4S-20	33,3	31	2,3
HDR 25	1"	25	45,0	47,7			37,0	404-16	SFA-4S-25	41,3	39	2,3
4-6 staalinlagen - Norm: SAE 100-R15 - Interlock												
ABT-6K-06	1/4	06	22,0	26,3	4		19,0	404-04	SFA-4S-06	18,3	16	2,3
ABT-6K-10	3/8	10	25,0	28,5			19,0	404-06	SFA-4S-10	22,0	19	3,0
ABT-6K-13	1/2	13	29,0	34,7			25,0	404-08	SFA-4S-13	26,3	23	3,3
Kunststof met 1 Nylon inlaag - Norm: SAE 100 R7												
CR 7-5	3/16	05	15,0	22,0	1			TP0-03	SFA-TP0-05	12,2	10	2,2
CR 7-6	1/4	06	17,0	29,0				0007-04	SF-78-06	14,0	14	0,0
CR 7-8	5/16	08	19,0	30,0				0007-05	SF-78-08	16,3	16	0,3
CR 7-10	3/8	10	21,0	31,0				0007-06	SF-78-10	18,3	16	2,3
CR 7-13	1/2	13	25,5	34,0				0007-12	SF-78-13	22,3	19	3,3
Kunststof slang met 1 staalinlaag												
CR 8-5	3/16	05	14,0	30,0	1			PX-255	PX 255	12,2	12	0,2
CR 8-6	1/4	06	18,0	30,0				001K-04H	SF-1K-06	15,0	14	1,0
CR 8-8	5/16	08	20,0	30,5				001K-05	SF-1K-08	17,0	16	1,0
CR 8-10	3/8	10	22,0	34,0				001K-06H	SF-1K-10	18,9	16	2,9
CR 8-13	1/2	13	25,5	34,0				001K-08H	SF-1K-13	22,3	19	3,3
Compact hogedruk reiniger slang Blauw - Norm: EN 857-1SC (Alfajet 210)												
SL 3010-06	1/4	06	17,0	26,5	1			TP0-04	SFA-TP0-06	13,4	12	1,4
SL 3010-08	5/16	08	19,0	26,5				TP0-05	SFA-TP0-08	15,2	14	1,2
SL 3010-10	3/8	10	22,0	26,5				TP0-06	SFA-TP0-10	17,8	16	1,8
SL 3010-13	1/2	13	26,0	30,5				TP0-08	SFA-TP0-13	21,5	19	2,5
Compact hogedruk reiniger slang Blauw - Norm: EN 857-2SC (Alfajet 400)												
SL 3020-06	1/4	06	19,0	25,5	2		19,0	SK1-04	SFA-SK1-06	16,1	16	0,1
SL 3020-08	5/16	08	21,0	25,5			19,0	SK1-05	SFA-SK1-08	18,0	16	2,0
SL 3020-10	3/8	10	23,0	27,5			20,0	SK1-06	SFA-SK1-10	19,9	19	0,9
SL 3020-13	1/2	13	27,0	33,5			26,0	SK1-08	SFA-SK1-13	24,0	23	1,0
Compact hogedruk reiniger slang Zwart - Norm: EN 857-2SC												
SL 560-08	5/16	08	21,0	25,5	2		19,0	SK1-05	SFA-SK1-08	18,0	16	2,0
SL 560-10	3/8	10	23,0	27,5			20,0	SK1-06	SFA-SK1-10	19,9	19	0,9
Compact hogedruk reiniger slang Geel - Norm: EN853-1SN - EN857-2SC												
SL3000-08	5/16	08	23,0	24,7	1			AD1-05	SFA-D1-08	18,3	16	2,3
SL3000-10	3/8	10	26,0	29,7				AD1-06	SFA-D1-10	21,0	19	2,0
SL3000-13	1/2	13	29,0	30,5				AD1-08	SFA-D1-13	24,4	23	1,4
SL4500-08	5/16	08	23,0	29,7	2			AD1-05	SFA-D1-08	19,0	19	0,0
SL4500-10	3/8	10	26,0	30,5				AD1-06	SFA-D1-10	21,6	19	2,6

Type slang	Doorlaat slang		Pershuls		Inlagen	Schillengte		Hulscode	Pershuls	Persdiameter	Pers- blok	Instelling
	inch	mm	Ø	mm		in	uit			Ø +/- 0,1 mm		
Aanzuig/retourslang - Norm: SAE 100-R4												
CR4-20	3/4	20	38,0	38,6	Helix			203-12	SFA-3TE-20	33,0	31	2,0
CR4-25	1"	25	50,0	45,3				203-16	SFA-3TE-25	41,1	39	2,1
CR4-32	1.1/4	32	51,0	49,0				203-20	SFA-3TE-32	44,5	39	5,5
CR6 slang - Norm: SAE 100 R6 - EN 854 R6												
CR 6-6	1/4	06	19,0	25,5	1			SK1-04	SFA-SK1-06	16,6	16	0,6
CR 6-8	5/16	08	21,0	25,5				SK1-05	SFA-SK1-08	18,7	16	2,7
CR 6-10	3/8	10	23,0	27,5				SK1-06	SFA-SK1-10	20,0	19	1,0
CR 6-13	1/2	13	27,0	33,5				SK1-08	SFA-SK1-13	24,0	23	1,0
CR 6-16	5/8	16	29,0	36,5				SK1-10	SFA-SK1-16	27,5	27	0,5
CR 6-20	3/4	20	33,0	40,0				SK1-12	SFA-SK1-20	31,3	31	0,3
CR 6-25	1"	25	41,0	46,5				SK1-16	SFA-SK1-25	37,8	31	6,8