

Type slang	Doorlaat slang		Pershuls		Inlagen	Schillengte		Hulscode	Pershuls	Persdiameter Ø +/- 0,1 mm	Pers- blok	Instelling
	inch	mm	Ø	mm		in	uit					
1 staalinlaag - dun rubber - Norm: EN 853-1SN / SAE 100 R1AT												
NST-HF 5	3/16	05	19,0	24,0	1			AD1-03	SFA-D1-05	14,8	14	4,2
NST-HF 6	1/4	06	22,0	24,7				AD1-04	SFA-D1-06	17,2	17	4,8
NST-HF 8	5/16	08	23,0	24,7				AD1-05	SFA-D1-08	18,9	17	4,1
NST-HF 10	3/8	10	26,0	29,7				AD1-06	SFA-D1-10	21,4	20	4,6
NST-HF 13	1/2	13	29,0	30,5				AD1-08	SFA-D1-13	24,7	24	4,3
NST-HF 16	5/8	16	32,0	30,5				AD1-10	SFA-D1-16	27,8	24	4,2
NST-HF 20	3/4	20	36,0	36,0				AD1-12	SFA-D1-20	31,7	28	4,3
NST-HF 25	1"	25	44,0	36,7				AD1-16	SFA-D1-25	39,4	32	4,6
NST-HF 32	1.1/4	32	53,0	48,6				AD1-20	SFA-D1-32	47,5	47	5,5
NST-HF 40	1.1/2	38	62,0	48,6				AD1-24	SFA-D1-40	54,4	54	7,6
NST-HF 50	2"	50	74,0	48,6				AD1-32	SFA-D1-50	68,0	67	6,0
2 staalinlagen - dun rubber - Norm: EN 853-2SN / SAE 100 R2AT												
HST-HF 5	3/16	05	21,0	24,0	2			AD2-03	SFA-D2-05	16,3	14	4,7
HST-HF 6	1/4	06	23,0	24,7				AD2-04	SFA-D2-06	18,2	17	4,8
HST-HF 8	5/16	08	25,0	24,7				AD2-05	SFA-D2-08	20,1	20	4,9
HST-HF 10	3/8	10	27,0	29,7				AD2-06	SFA-D2-10	22,3	20	4,7
HST-HF 13	1/2	13	30,0	30,5				AD2-08	SFA-D2-13	25,4	24	4,6
HST-HF 16	5/8	16	33,0	30,5				AD2-10	SFA-D2-16	28,8	28	4,2
HST-HF 20	3/4	20	37,0	36,0				AD2-12	SFA-D2-20	32,5	32	4,5
HST-HF 25	1"	25	45,0	36,7				AD2-16	SFA-D2-25	39,9	40	5,1
HST-HF 32	1.1/4	32	56,0	48,6				AD2-20	SFA-D2-32	49,6	47	6,4
HST-HF 40	1.1/2	38	64,0	48,5				AD2-24	SFA-D2-40	56,7	54	7,3
HST-HF 50	2"	50	77,0	48,6				AD2-32	SFA-D2-50	70,8	67	6,2
1 staalinlaag compact slang - Norm: EN 857-1SC												
NSK 6	1/4	06	22,0	24,7	1			AD1-04	SFA-D1-06	16,5	14	5,5
NSK 8	5/16	08	23,0	24,7				AD1-05	SFA-D1-08	18,1	17	4,9
NSK 10	3/8	10	26,0	29,7				AD1-06	SFA-D1-10	20,4	20	5,6
NSK 13	1/2	13	29,0	30,5				AD1-08	SFA-D1-13	23,9	24	5,1
2 staalinlagen compact slang - Norm: EN 857-2C												
HSK-HF 6	1/4	06	22,0	24,7	2			AD1-04	SFA-D1-06	17,4	17	4,6
HSK-HF 8	5/16	08	23,0	24,7				AD1-05	SFA-D1-08	19,1	17	3,9
HSK-HF 10	3/8	10	26,0	29,7				AD1-06	SFA-D1-10	21,2	20	4,8
HSK-HF 13	1/2	13	29,0	30,5				AD1-08	SFA-D1-13	24,8	24	4,2
HSK-HF 16	5/8	16	32,0	30,5				AD1-10	SFA-D1-16	27,9	24	4,1
HSK-HF 20	3/4	20	36,0	36,0				AD1-12	SFA-D1-20	31,7	28	4,3
HSK-HF 25	1"	25	44,0	36,7				AD1-16	SFA-D1-25	39,4	32	4,6

Type slang	Doorlaat slang		Pershuls		Inlagen	Schillengte		Hulscode	Pershuls	Persdiameter	Pers-blok	Instelling	
	inch	mm	Ø	mm		in	uit			Ø +/- 0,1 mm			
2 staalinlagen compact slang - Exceeds Norm: EN 857-2SC - SAE 100-R16													
HSK-PQ 6	1/4	06	22,0	24,7	2			AD1-04	SFA-D1-06	17,4	17	4,6	
HSK-PQ 8	5/16	08	23,0	24,7				AD1-05	SFA-D1-08	18,9	17	4,1	
HSK-PQ 10	3/8	10	26,0	29,7				AD1-06	SFA-D1-10	21,3	20	4,5	
HSK-PQ 13	1/2	13	29,0	30,5				AD1-08	SFA-D1-13	25,1	24	3,9	
HSK-PQ 16	5/8	16	32,0	30,5				AD1-10	SFA-D1-16	27,9	24	4,1	
HSK-PQ 20	3/4	20	36,0	36,0				AD1-12	SFA-D1-20	31,7	28	4,3	
HSK-PQ 25	1"	25	44,0	36,7				AD1-16	SFA-D1-25	39,8	40	4,2	
HSK-PQ 32	1.1/4	32	53,0	48,6				AD1-32	SFA-D1-32	47,1	44	5,9	
HSK-PQ 40	1.1/2	38	61,0	48,6				AD1-40	SFA-D1-40	54,7	50	6,3	
HSK-PQ 50	2"	50	75,0	48,6				AD1-50	SFA-D1-50	68,5	71	6,5	
4 staalinlagen - skive - Norm: SAE 100 R9R / DIN 20023 - 4SP / EN 856-4SP													
HDR 6	1/4	06	22,0	26,3	4		19,0	404-04	SFA-4S-06	18,5	17	3,5	
HDR 10	3/8	10	25,0	28,5			19,0	404-06	SFA-4S-10	22,1	20	2,9	
HDR 13	1/2	13	29,0	34,7			25,0	404-08	SFA-4S-13	26,4	24	2,6	
HDR 16	5/8	16	33,0	37,5			28,0	404-10	SFA-4S-16	29,2	28	3,8	
HDR 20	3/4	20	37,0	41,5			33,0	404-12	SFA-4S-20	33,3	32	3,7	
HDR 25	1"	25	45,0	47,7			37,0	404-16	SFA-4S-25	41,3	40	3,7	
HDR 32	1 1/4	32	58,0	54,5			41,0	404-20	SFA-4S-32	52,7	50	5,3	
HDR 40	1 1/2	38	67,0	61,1			47,0	404-24	SFA-4S-40	61,5	57	5,5	
HDR 50	2"	50	82,0	75,1			60,0	404-32	SFA4S-50	76,5	74	5,5	
4 staalinlagen - skive - Norm: EN 856-4SH - Interlock													
4SH-20	3/4	20	38,0	60,1	4	15,0	50,0	H1400200-12	SFA-4H-20	34,0	32	4,0	
4SH-25	1"	25	46,0	74,6		17,0	65,0	H1400200-16	SFA-4H-25	42,1	40	3,9	
4SH-32	1.1/4	32	55,0	88,1		21,5	74,0	H1400200-20	SFA-4H-32	51,1	50	3,9	
4SH-40	1.1/2	38	62,0	94,1		22,0	81,0	H1400200-24	SFA-4H-40	57,1	57	4,9	
4SH-50	2"	50	78,0	99,1		29,0	85,0	H1400200-32	SFA-4H-50	73,0	71	5,0	
4-6 staalinlagen - Norm: SAE 100-R15 - Interlock													
AT6KR15-16	5/8	16	35,5	57,5	4	15,0	45,0	H1400301-10	SFA-R15-16	31,7	28	3,8	
AT6KR15-20	3/4	20	38,0	60,1		15,0	52,0	H1400200-12	SFA-4H-20	34,0	32	4,0	
AT6KR15-25	1"	25	46,0	74,6		17,0	65,0	H1400200-16	SFA-4H-25	42,2	40	3,8	
AT6KR15-32	1.1/4	32	62,0	88,1	6	21,5	74,0	H1400301-20	SFA-R15-32	55,8	54	6,2	
AT6KR15-40	1.1/2	38	69,5	94,1		22,0	81,0	H1400301-24	SFA-R15-40	63,6	62	5,9	
4-6 staalinlagen - Norm: SAE 100-R15 - Interlock Alfa Biotech													
ABT-6K-06	1/4	06	22,0	26,3	4		19,0	404-04	SFA-4S-06	18,3	16	3,7	
ABT-6K-10	3/8	10	25,0	28,5			19,0	404-06	SFA-4S-10	22,0	20	3,0	
ABT-6K-13	1/2	13	29,0	34,7			25,0	404-08	SFA-4S-13	26,3	26	2,7	
ABT-6K-16	5/8	16	35,5	57,5			15,0	45,0	H1400301-10	SFA-R15-16	31,7	30	3,8
ABT-6K-20	3/4	20	38,0	60,1			15,0	52,0	H1400200-12	SFA-4H-20	34,0	34	4,0
ABT-6K-25	1"	25	46,0	74,6			17,0	65,0	H1400200-16	SFA-4H-25	41,7	39	4,3
ABT-6K-32	1 1/4	32	62,0	88,1		6	21,5	74,0	H1400301-20	SFA-R15-32	55,6	51	6,4
ABT-6K-40	1 1/2	38	69,5	94,1	22,0		81,0	H1400301-24	SFA-R15-40	63,2	63	6,3	

Type slang	Doorlaat slang		Pershuls		Inlagen	Schillengte		Hulscode	Pershuls	Persdiameter	Pers- blok	Instelling	
	inch	mm	Ø	mm		in	uit			Ø +/- 0,1 mm			
Kunststof met 1 Nylon inlaag - Norm: SAE 100 R7													
CR 7-5	3/16	05	15,0	22,0	1			TP0-03	SFA-TP0-05	12,2	12	2,8	
CR 7-6	1/4	06	17,0	29,0				0007-04	SF-78-06	14,0	14	3,0	
CR 7-8	5/16	08	19,0	30,0				0007-05	SF-78-08	16,3	14	2,7	
CR 7-10	3/8	10	21,0	31,0				0007-06	SF-78-10	18,3	17	2,7	
CR 7-13	1/2	13	25,5	34,0				0007-12	SF-78-13	22,3	20	3,2	
Kunststof slang met 1 staalinlaag													
CR 8-5	3/16	05	14,0	30,0	1			PX-255	PX 255	12,2	12	1,8	
CR 8-6	1/4	06	18,0	30,0				001K-04H	SF-1K-06	15,0	14	3,0	
CR 8-8	5/16	08	20,0	30,5				001K-05	SF-1K-08	17,0	17	3,0	
CR 8-10	3/8	10	22,0	34,0				001K-06H	SF-1K-10	18,9	17	3,1	
CR 8-13	1/2	13	25,5	34,0				001K-08H	SF-1K-13	22,3	20	3,2	
Compact hogedruk reiniger slang Blauw - Norm: EN 857-1SC (Alfajet 210)													
SL 3010-06	1/4	06	17,0	26,5	1			TP0-04	SFA-TP0-06	13,4	12	3,6	
SL 3010-08	5/16	08	19,0	26,5				TP0-05	SFA-TP0-08	15,2	17	3,8	
SL 3010-10	3/8	10	22,0	26,5				TP0-06	SFA-TP0-10	17,8	20	4,2	
SL 3010-13	1/2	13	26,0	30,5				TP0-08	SFA-TP0-13	21,5	24	4,5	
Compact hogedruk reiniger slang Blauw - Norm: EN 857-2SC (Alfajet 400)													
SL 3020-06	1/4	06	19,0	25,5	2		19,0	SK1-04	SFA-SK1-06	16,1	14	2,9	
SL 3020-08	5/16	08	21,0	25,5			19,0	SK1-05	SFA-SK1-08	18,0	17	3,0	
SL 3020-10	3/8	10	23,0	27,5			20,0	SK1-06	SFA-SK1-10	19,9	20	3,1	
SL 3020-13	1/2	13	27,0	33,5			26,0	SK1-08	SFA-SK1-13	24,0	24	3,0	
Compact hogedruk reiniger slang Zwart - Norm: EN 857-2SC													
SL 560-08	5/16	08	21,0	25,5	2		19,0	SK1-05	SFA-SK1-08	18,0	17	3,0	
SL 560-10	3/8	10	23,0	27,5			20,0	SK1-06	SFA-SK1-10	19,9	20	3,1	
Compact hogedruk reiniger slang Geel - Norm: EN853-1SN - EN857-2SC													
SL3000-08	5/16	08	23,0	24,7	1			AD1-05	SFA-D1-08	18,3	17	4,7	
SL3000-10	3/8	10	26,0	29,7					AD1-06	SFA-D1-10	21,0	20	5,0
SL3000-13	1/2	13	29,0	30,5					AD1-08	SFA-D1-13	24,4	24	4,6
SL4500-08	5/16	08	23,0	29,7	2			AD1-05	SFA-D1-08	19,0	17	4,0	
SL4500-10	3/8	10	26,0	30,5					AD1-06	SFA-D1-10	21,6	20	4,4
Aanzuig/retourslang - Norm: SAE 100-R4													
CR4-20	3/4	20	38,0	38,6	Helix			203-12	SFA-3TE-20	33,0	32	5,0	
CR4-25	1"	25	50,0	45,3					203-16	SFA-3TE-25	41,1	40	8,9
CR4-32	1.1/4	32	51,0	49,0					203-20	SFA-3TE-32	44,5	44	6,5
CR4-40	1.1/2	38	60,3	56,0					203-24	SFA-3TE-40	51,8	50	8,5

Type slang	Doorlaat slang		Pershuls		Inlagen	Schillengte		Hulscode	Pershuls	Persdiameter	Pers- blok	Instelling
	inch	mm	Ø	mm		in	uit			Ø +/- 0,1 mm		
CR6 slang - Norm: SAE 100 R6 - EN 854 R6												
CR 6-6	1/4	06	19,0	25,5	1			SK1-04	SFA-SK1-06	16,6	14	2,4
CR 6-8	5/16	08	21,0	25,5				SK1-05	SFA-SK1-08	18,7	17	2,3
CR 6-10	3/8	10	23,0	27,5				SK1-06	SFA-SK1-10	20,0	20	3,0
CR 6-13	1/2	13	27,0	33,5				SK1-08	SFA-SK1-13	24,0	24	3,0
CR 6-16	5/8	16	29,0	36,5				SK1-10	SFA-SK1-16	27,5	24	1,5
CR 6-20	3/4	20	33,0	40,0				SK1-12	SFA-SK1-20	31,3	28	1,7
CR 6-25	1"	25	41,0	46,5				SK1-16	SFA-SK1-25	37,8	32	3,2